FEMALE END VIEW



	1. VT
	2. RD
	3. GY
	4. RD/BU
	5. GN
13.YE/BN	6. BU
14.BN/GN	7. GY/PK
15.WH	8. WH/GN
16.YE	9. WH/YE
17.PK	10.WH/GY
18.GY/BN	11.BK
19.BN	12.GN/YE

HARTING P/N	Type of cable	Cable length(mm)
21373600D74050	PUR	5000^{+200}_{-0}
21373600D74100	PUR	10000^{+400}_{-0}

SPECIFICATIONS	
CONTANCT CARRIER MATERIAL/COLOR	PBT/WHITE
MOLDED HEAD MATERIAL/COLOR	TPU/BLACK
CONTACT MATERIAL/COLOR	BRASS/SILVER
COUPLING NUT MATERIAL/PLATING	ZINC ALLOY/NICKEL
RATED CURRENT	9A(PINS 6,12,19),2A(ALL OTHERS)
RATED VOLTAGE	150 V
OUTER CABLR JACKET MATERIAL/COLOR	PUR/BLACK
CONDUCTOR INSULATION MATERIAL	PVC
NUMBER OF CONDUCTORS (AWG)	3X18AWG+16X22AWG
OPERATING TEMPERATURE	-40°C — +80°C
PROTECTION CLASS	IEC IP67



All Dimensions in mm	Tech. Character.	Free size tol.	According to production drawing		
All rights reserved	Created by LINI	Inspected by LIANL	Standardisation LIANL	Date 2022-11-02	State Final release
Department HCS - CN	Title M23_19P FE,Int-thread,ANG PUR cable,xxM				Doc-Key / ECM-Nr. /
HARTING Customised Solutions D-32339 Espelkamp	Type TB	Number 2137 36 00 D 74 XXX		Rev. A	Page 1/1

Rev.	Description	Appr.	Date
A	First issue.	Ivy Lin	11/02/22

A4