

1		2		3		4		5		6	
FEMALE END VIEW								SPECIFICATIONS			
A 1. VT 2. RD 3. GY 4. RD/BU 5. GN 6. BU 7. GY/PK 8. WH/GN 9. WH/YE 10. WH/GY 11. BK 12. GN/YE 13. YE/BN 14. BN/GN 15. WH 16. YE 17. PK 18. GY/BN 19. BN shield		HARTING P/N		Type of cable		Cable length(mm)		CONTANCT CARRIER MATERIAL/COLOR		PBT/WHITE	
		21373600D75050		PVC		5000 ⁺²⁰⁰ ₋₀		MOLDED HEAD MATERIAL/COLOR		TPU/BLACK	
		21373600D75100		PVC		10000 ⁺⁴⁰⁰ ₋₀		CONTACT MATERIAL/COLOR		BRASS/SILVER	
								COUPLING NUT MATERIAL/PLATING		ZINC ALLOY/NICKEL	
								RATED CURRENT		9A(PINS 6,12,19),2A(ALL OTHERS)	
								RATED VOLTAGE		150 V	
								OUTER CABLR JACKET MATERIAL/COLOR		PVC/BLACK	
								CONDUCTOR INSULATION MATERIAL		PVC	
								NUMBER OF CONDUCTORS (AWG)		3X18AWG+16X22AWG	
								OPERATING TEMPERATURE		-40°C — +80°C	
						PROTECTION CLASS		IEC IP67			
B											
C		73.2 100±5 50.2 M23X1 Ø26 SHIELD CONNECTED TO COUPLING 10±3 *M									
D											